



Pipe grinders & Pipe notchers

The art to make the technique work



AL 150HS

ALM PIPE GRINDERS

ALMI Pipe grinders offer you added value through the security of years of trouble-free, accurate and to edit pipes fast. Because ALMI sells the pipe grinders worldwide in 60 different countries, this proves the guarantee of high-quality products. In addition, ALMI strives for continuity of product development processes and innovations. To provide you with the most recent and best developed pipe grinders at all times.

ALMI Pipe grinders are solid build, because ALMI Pipe grinders guarantee: these machines run at high speeds. Therefore - Stable and accurate working the stability is a major influence on the final - Fast and almost heat-free grinding of result. Processing stainless steel profiles and pipes at high speeds goes smoothly and fast. - No grinding frames and discoloration And without grinding burrs and discoloration of the material. Changing grinding belts can be - Grinding rolls that can be exchanged done quickly. No tools are required, therefore you save a lot of valuable work time.

Multifunctional

Replacing the grinding belt is also simple and - Cutting out any desired material can be done on one side of the machine. After - Grind any desired diameter at any desired grinding of profiles and pipes, they can be burred on the handy burring table at the top or - Success, durability and high quality back of the machine. The ALMI machines with lever control are both suitable for left-handed - Optional length stop and right-handed employees. With a simple - Possibility to grind from the center by operation, the lever can be placed both sides, right and left.

- stainless steel
- of the material
- quickly without tools
- Quick change of grinding belts
- Handy burring by means of a burring table
- Left-handed and right-handed use
- angle between 20°-90°
- composite materials
- means of optional filler plates
- Quick change from lever to handwheel operation within 1 minute

Thousands of satisfied users have already experienced it, ALMI machines are an investment that makes you money!

Benefits

- Grinds any desired diameter
- Grinds all common materials
- Tubes and profiles
- Very accurate
- Sustainable
- Cuts inconel and aluminum
- Connection point for dust extraction
- Can be operated with one key





video here

TECHNICAL SPECIFICATIONS AL 150HS Engine 4KW 230V 3F 400V 3F of 460V 3F Voltages Belt speed 45 meter p/sec. /4300 rpm Belt size 150x2000 mm 20,0 / 114,3 mm **Grinding diameters** Grinding angle 20° - 90° Weight 275 kg. Operation Lever and handwheel operation Dimensions 1450x1260x900 mm



AL 150 AL 100U-01 / 02



TECHNICAL SPECIFICATIONS AL 150			
Engine	4KW		
Belt speed	30 meter p/sec./2800 rpm		
Belt size	150x2000 mm		
Grinding diameters	20,0 / 114,3 mm		
Grinding angle	20° - 90°		
Weight	260 kg.		
Operation	Lever and handwheel operation		
Dimensions	1450x1200x850 mm		



TECHNICAL SPECIFICATIONS AL 100U-01 / AL 100U-02		
Engine	3KW	
Belt speed	30 meter p/sec./2800 rpm	
Belt size	100x2000 mm	
Grinding diameters	20,0 / 76,1 mm	
Grinding angle	30° - 90°	
Weight	AL 100U-01 190 kg. / AL 100U-02 220 kg.	
Operation	AL 100U-01 Only lever operation AL 100U-02 Lever and handwheel operation	
Dimensions	1450x1150x650 mm	



ALMI HIGH SPEED

Striving for maximum production

ALMI is the inventor of the pipe grinder and the pipe notcher. The AL 150 High Speed is the new 2 in 1 machine: grinding machine and pipe grinder in one. This machine has a unique transmission that brings the belt speed to 45 meters per second. As a result, you grind 3 times faster and the grinding belt has up to 3 times longer life than other grinders. This machine is suitable for steel, stainless steel, aluminum, inconel and plastics.

Benefits

- + Grinds 45 meters p/sec. belt speed 4300 rpm.
- Grinds any desired diameter
- + Grinds all common materials, incl. aluminum and inconel
- + Pipes, tubes, profiles and strips
- No fine dust
- No discoloration
- + 3 times longer life of grinding belts
- + With optional dust extraction
- Optional lifting plates
- Optional length stop
- + 1400 rpm 30 sec. / 4300 rpm 6 sec. grinding time





watch the video here

"The dust extraction is optional to assemble on each pipe grinder"







ALMI PIPE NOTCHERS

The right notcher for every application

Almi is the inventor of the pipe notcher. In industries where pipes and profiles are welded together at an angle of 90°, ALMI Pipe notchers ensure the right recess extremely quickly and precisely. This applies to gas, steam, stainless steel, non-ferrous pipes and profile materials.

ALMI Pipe notchers are also very suitable ALMI Pipe notchers guarantee: for making double-corner connections. - High productivity In addition, ALMI supplies a notcher for - A simple and quick operation notching a sink outflow in round and - Machining multiple diameters with one tool rectangular metal tubes.

ALMI Pipe notchers are an added value - High-quality composite materials and offer you the assurance of years of trouble-free, accurate and fast processing Thousands of satisfied users have already of tubes and profiles. Because ALMI sells experienced it, ALMI machines are an the pipe notchers worldwide in 60 different investment that makes money for you! ALMI countries, this proves the guarantee of high- Pipe grinders and ALMI Pipe notchers are quality products. In addition, ALMI strives for investments with a return! continuity of product development processes and innovations. To offer you the most recent and best developed pipe notchers at all times.

- Make double corner connections without any problems
- Success and sustainability



Benefits

- High productivity
- Low investment
- Simple and fast operation
- Ideal for double corner connections
- + Also for sink outflow



AL 1-2E



TECHNICAL SPECIFICATIONS

26,9 mm / 3/4" 33.7 mm / 1" 42,4 mm / 11/4" Tube diameter 48,3 mm / 1½" 60,3 mm / 2"

Sink outflow

Electrically powered

230/400/575 Volt

X

Maximum wall thickness

5 mm steel 3 mm stainless steel

87 kg. Weight

AL 1-2-U



TECHNICAL SPECIFICATIONS

26.9 mm / 3/4" 33,7 mm / 1" 42,4 mm / 11/4" Tube diameter 48,3 mm / 1½" 60,3 mm / 2" Sink outflow 20 - 76,1 mm Electrically powered 230/400/575 Volt 5 mm steel Maximum wall thickness 3 mm stainless steel

93 kg. Weight



AL 1





TECHNICAL SPECIFICATIONS

26,9 mm / ¾"
Tube diameter 33,7 mm / 1"
42,4 mm / 1¼"

Maximum wall thickness 3 mm steel 2,5 mm stainless steel

Weight 8 kg.



AL 2



TECHNICAL SPECIFICATIONS

Tube diameter 48,3 mm / 1^{1/2"} 60,3 mm / 2"

Maximum well this lenges 3 mm steel

Maximum wall thickness 2,5 mm steel 2,5 mm stainless steel

Weight 15 kg.



TECHNICAL SPECIFICATIONS

Tube diameter 42,4 mm / 11/4" 48,3 mm / 11/2"

Maximum wall thickness 3 mm steel

2,5 mm stainless steel

Weight 15 kg.

ALU



TECHNICAL SPECIFICATIONS

Tube diameter 20-76,1 mm

Maximum wall thickness 3 mm steel

2,5 mm stainless steel

Weight 7 kg.



THEREFORE ALMI

EUROTRUSS CAN REACT FASTER TO THE MARKET BECAUSE OF THE ALMI HIGH SPEED

Eurotruss is worldwide supplier of Truss with the production location in Leeuwarden. The high speed of the AL 150HS is ideally suited for aluminum processing for Eurotruss.

Because the aluminum is not burned, but freshly polished, it is directly applicable for welding.





ALMI HIGH SPEED MAKES PROCESSING INCONEL A CONVENIENCE FOR STORK

For Stork Hengelo it was not possible for years to process inconel easily. The ALMI High Speed changed that.

Inconel is a product that is used in incinerators. It is a hard and wear-resistant material. With Stork it has become possible with the arrival of the AL 150HS to process inconel in a fast and very simple way.





THE ALMI HIGH SPEED IS INDISPENSABLE IN THE MEASURING PRODUCTION OF MFABRICATIONS

MFabrications based in St. Jansteen in Zeeland, manufactures a variety of metal constructions and specializes in the production of roll cages and suspensions for motorsports.

What MFabrications says about the ALMI High Speed: "Thanks to its excellent quality and minimal changeover times, the machine is now an integral part of our customized production. The threefold lifespan of the grinding belts play an important role in this".





FREE WITH EVERY PIPE GRINDER:

- hexagonal key
- grinding roll 42,4 mm
- 5 stretch-free grinding belts

The grinding belt is unique because it is stretch-free during grinding. Due to this the belt tension remains equal. In addition these grinding belts are suitable for all materials.

Of course you can order these grinding belts per 5 or 10 pieces trhough our webshop **WWW.ALMI.NL**





The right **ALMI** product in the right place

ALMI Pipe notchers







	AL 1, AL 2, AL 3	AL 1-2E, AL 1-2-U	ALU
Possible profiles			
Right/variable angel	上	느	뇨
Eccentric editing	-	-	-
Tube diameter*	AL 1 26,9 mm / ¾" 33,7 mm / 1" 42,4 mm / 1¼" AL 2 48,3 mm / 1½" 60,3 mm / 2" AL 3 42,4 mm / 1¼" 48,3 mm / 1½"	26,9 mm / ³ / ₄ " 33,7 mm / 1" 42,4 mm / 11/4" 48,3 mm / 11/2" 60,3 mm / 2"	20 mm - 76,1 mm
Maximum wall thickness	3 mm steel and 2,5 mm stainless steel	5 mm steel and 3 mm stainless steel	3 mm steel and 2,5 mm stainless steel
Sink outflow	-	AL 1-2-U 🗸	✓
Grinding belt	-	-	-
Handwheel/Lever	-	-	-
Electrical operation	-	\checkmark	-
3 year warranty**	✓	✓	✓
Dust extraction	-	-	-
Length stop	-	-	-

ALMI Pipe grinders









AL 100-U01

AL 100-U02

AL 150

AL 150HS











30° till 90°

20 mm - 76,1 mm

30° till 90°

20 mm - 76, 1mm

20° till 90°

20° till 90°

20 mm - 114,3mm

20 mm - 114,3mm

Inapplicable

Inapplicable

Inapplicable

Inapplicable

100 mm x 2000 mm

150 mm x 2000 mm

150 mm x 2000 mm

Lever

Lever and handwheel

100 mm x 2000 mm

Lever and handwheel

Lever and handwheel













Optional

Optional

Optional

Optional

Optional

Optional

Optional

Optional

Other sizes on request Warranty of 3 years upon registration. Normal warranty 1 year



The art to make the technique work



More info?

Visit our website www.ALMI.NL



