



## B2 AIR deburring system

Maximum bevel width 2 mm / 0.08 in. Edge rounding function.

# B2 Air

Art. Nr. 24200



Ergonomic body of the machine

Weight only 400g

Precise scale of machining depth adjustment





**Designed for deburring and rounding edges of steel, stainless steel, aluminum and other workpieces. Suitable for machining holes from the internal diameter of 6.8 mm / 0.24 in.**

- The compact design offers great ergonomics.
- Weight only 400 g / 0.88 lb.
- Edge machining by rounding R1.5 mm / 0.06 in - edge preparation before painting.
- Powerful and reliable pneumatic drive.
- Precision machining scale allows for more precise machining.

**Technical data:**

|                            |  |
|----------------------------|--|
| Bevel angle:               | 45°                                    |
| Bevel width (hypotenuse):  | 2 mm / 0.08 in as a maximum            |
| Rounding radius:           | R 1,5 mm / 0.06 in                     |
| Speed                      | 23,000 rpm.                            |
| Feeding:                   | manual                                 |
| Air consumption            | 320 l/min                              |
| Dimensions:                | 112 x 60 x 48 mm / 4.4 x 2.36 x 1.9 in |
| Weight:                    | 400 g / 0.88 lb                        |
| Number of cutting inserts: | 3 pcs                                  |

**Included in price:**

B2 AIR deburring system - fitted with head with cutting inserts.  
Tools for an operators.  
Packed in a cardboard.  
User manual.



**Machine name:**

B2 AIR deburring system - fitted with head with cutting inserts

**Art. Nr.**

24200



**Accessories:**

|  | <b>Art. Nr.</b> |
|--|-----------------|
| Inserts B2 AIR (pack of 10 pcs)  | 24201           |
| Inserts radius R1.5mm (pack of 10 pcs)   | 24202           |
| Inserts B2 AIR, coated (pack of 10 pcs)  | 24204           |
| Pneumatic set with quick couplings (contains: FRL - filtration, regulator and lubrication unit, quick couplings, hoses 10 m) | 24203           |
| Screw for the inserts  | 7252F-04        |



Art. Nr. 24203



Art. Nr. 24201



Art. Nr. 24204



Art. Nr. 24202

