



PRECISION BENDING, SIMPLIFIED



POWERFUL,
PRECISE &
RELIABLE

PLATE BENDING MACHINES

PB3 & PB4 SERIES

PLATE BENDING

All our Plate rolls are custom built and engineered with years of experience to have the maximum drive torque throughout the entire speed range, unlike many competitors who only have maximum drive torque available at low speed. We only use hydraulic drive as standard for all models to help the operator produce the best bending results. A SweBend machine will result in the highest ROI compared to any competitive machine.

HIGHER POWER → FEWER PASSES → HIGHER PRODUCTION CAPACITY → HIGHER PROFIT → SHORTER PAY-OFF



“ELIMINATE” FLAT ENDS

Through Swedish engineering SweBend has proven to be THE best at virtually eliminating flat ends. Our machines produce high enough forces from the bending rolls to reduce the flat ends to a bare minimum.

No matter what anyone tells you, in the end, reducing the length of flat ends comes down to raw bending force, and SweBend uses world-renowned Swedish manufacturing standards and unmatched competence to produce the strongest machines with the highest roll power on the market.



THE BEST ROLLS FOR AMAZING RESULTS

Our rolls are induction hardened roll forgings produced by well-known German steel mills such as DiroStahl. The roll material is ALWAYS individually tailored to meet our customer's exact requirements which gives the best precision, durability and quality.



RAZOR SHARP BENDING PRECISION THROUGH ELECTRONIC ROLL

For outstanding bending precision, our plate bending machines are equipped with a razor sharp roll parallelism control system with a tolerance of $\pm 0.1 \text{ mm}$ (0.004"). This precision parallel system is powered by control systems from Beckhoff, a leader in industrial automation and controls.




MADE IN SWEDEN - BECAUSE QUALITY MATTERS

Means a machine that guarantees the highest quality in all details resulting in longer lifetime, less maintenance and repairs, higher output, better production quality and an unmatched return-on-investment!

DESIGNED THROUGH EXPERIENCE

All machine sizes are designed with the know-how SweBend engineers achieved over a long period of years and with extra attention to even the smallest details that truly will make a big difference in the long run. Anyone can build a plate roll but very few know what is required to achieve market-leading performance, and make it last for decades!



POWERFUL, PRECISE & RELIABLE

SweBend designs and produces the strongest and most user-friendly machines on the market. You can be sure to get the highest drive torque and strongest bending power compared to any other Plate roll of the same size.

A SWEBEND MACHINE IS A MACHINE WHICH...

- ✓ has the lowest total cost of ownership of any competitive machine.
- ✓ is customized to meet each customer's specific requirements. We use our vast knowledge to dimension each part of the machine to be balanced perfectly for our customer.
- ✓ has bearings from SKF (the world famous Swedish bearing company) throughout the entire machine which will keep rolling, rolling and rolling!
- ✓ has cutting edge quality and induction hardened roll forgings from well-known German steel mills.
- ✓ has top hydraulic and electronic components from the best suppliers.
- ✓ has heavily proportioned frame and mechanical parts.



SPECIAL REQUIREMENTS

With our standard range of models as a foundation, we design and produce custom-built and adapted plate rolls for specific customer needs. This can mean producing a machine with a unique roll diameter, special roll length or even a customized shape of the rolls. Request help with integrating the machine in your product line, demand special features and ask for what you think is impossible; we'll gladly prove you wrong!



THE PB3 SERIES

PLATE BENDING / PLATE ROLLS WITH 3 ROLLS

Perfect for bending companies and job shops
(see the **PB4** for machines for production applications).

The **PB3** (Plate Bending 3 roll) series is the strongest 3 roll machine ever made. These are versatile and universal machines. Through advanced engineering and knowledge of components, we can guarantee the highest prebending power and drive torque compared to all similar sized machines on the market. The bending roll power is the key factor in bending.

SweBend has developed a new complete standard range of three roll plate bending machines, starting with the PB3-4-500 (top roll Ø100 mm (4"), length 500 mm and stretching all the way up to the giant PB3-42-14 (top roll 1060 mm (42"), length 4300 mm (14"). We will of course also deliver other lengths, shorter as well as longer, up to 8000 mm (26") length. Our standard machines handle plate thickness range 1 mm – 250 mm (18 ga. – 10"), in virtually any grade of steel or other material.

MADE IN SWEDEN - BECAUSE QUALITY MATTERS



STANDARD FEATURES

- Double-pinch pyramid design, enabling prebending at both ends of the plate
- Razor sharp electronic control of roll parallelism (+/- 0.1 mm (0.004") tolerance)
- Wireless control unit with variable speed joysticks and digital readouts
- Hardened & ground rolls with polished roll finish
- Easy prebending and rolling in either direction
- Tilttable bending rolls
- Variable rotation speed
- Four digital readouts (one for each end of both lower rolls)
- 3 hydraulically driven rolls
- SKF bearings only
- Top electrical & hydraulic components from the best suppliers
- Hydraulic opening mechanism (drop end) for unloading finished rolled product
- Emergency stop devices
- CE-Certification

OPTIONAL FEATURES

- Customized roll crowning
- Special rolls with contour, grooves etc., to allow bending plates with flanges and/or ribs
- Changeable top roll for rolling diameters smaller than possible with the standard top roll (Extra Top Roll)
- Cone bending device (key or roll)
- Special color and design
- Oil cooling system
- Top support/lifting device with electro-mechanical or hydraulic operation
- Side supports
- Calibration Systems
- And much, much more...

EXPLORE THE PB3 SERIES FURTHER ONLINE:



Website

Youtube



SEE THE PB3 CAPACITY TABLE ON PAGE 8 ➔

THE PB4 SERIES

PLATE BENDING / PLATE ROLLS WITH 4 ROLLS

Perfect for bending companies and production applications.


The **PB4** (Plate Bending 4 roll) series with the optional SweBend SEVEN CNC system is ideal for repetitive series production. The double pinch bending mechanism allows for optimal results in only one pass, which equals reduced production time! The bending precision and ease of use allows for the mass production of complex shapes and radii transitions. Through advanced engineering and knowledge of components we can guarantee the highest prebending power and drive torque compared to all similar sized machines on the market.

The PB4 series from SweBend offers twelve different standard size ranges, from PB4-4 with top roll diameter 102 mm (4") up to PB4-28 with top roll diameter 711 mm (28"). With roll lengths from 500 mm (20") up to 8 000 mm (26'), SweBend will always offer the best machine.

 **MADE IN SWEDEN - BECAUSE QUALITY MATTERS**

CUSTOMIZED FOR YOUR APPLICATION.

All machines are designed and engineered using the latest 3D CAD systems, are heavily proportioned, and have more bending power compared to any other plate bending machine on the market. Our machines handle plate thickness in the range 1mm – 250mm (18 ga. – 10"), in virtually any grade of steel or other material.



SEE THE PB4 CAPACITY TABLE ON PAGE 9 ➔

EXPLORE THE PB4 SERIES FURTHER ONLINE:



Website



Youtube

STANDARD FEATURES

- Double-pinch design, enabling prebending at both ends of the plate
- Razor sharp electronic control of roll parallelism (+/-0.1 mm (0.004") tolerance)
- Wireless control unit with variable speed joy sticks and digital readouts
- Hardened & ground rolls with polished finish
- Easy prebending and rolling in either direction
- Tilttable bending rolls
- Variable rotation speed
- Four digital readouts (both ends of both side rolls)
- Top and lower roll hydraulically driven
- SKF bearings only
- Top electrical & hydraulic components from the best suppliers
- Hydraulic opening mechanism (drop end) for unloading finished rolled product, including hydraulic raising of the top roll when the drop end is opened (optional on PB4-4 models)
- Emergency stop devices
- CE-Certification

OPTIONAL FEATURES

- Customized roll crowning
- Support rolls under the lower roll
- SEVEN – SweBend's own trademarked Graphical CNC SYSTEM
- "Turbo Production" kits in combination with CNC
- Special rolls with contour, grooves etc., to allow bending plates with flanges and/or ribs
- Integration in production cells, including communication with other software systems
- Changeable top roll for rolling diameters smaller than possible with the standard top roll
- Cone bending device (key or roll)
- Material ejection devices
- Plate handling equipment and robot loading (infeed tables, lifters & loaders)
- Special color and design
- Calibration Systems
- Side supports
- Top support with electro-mechanical or hydraulic operation
- And much, much more...

CAPACITY TABLE PB3

Our machine sizes can handle plate thickness 1 - 250 mm (18 ga. – 10”).

We will guide you to the right machine to meet your specific requirements.

Don’t worry – we can bend almost everything!

		ROLL DIAMETERS		PREBENDING	CIRCULAR ROLLING		
MODEL	ROLL LENGTH	TOP	BOTTOM	PB 3*TRD	RB 5*TRD	RB 8*TRD	MOTOR SIZE
	mm	mm	mm	mm	mm	mm	kW
PB3-6-3	1000	152	152	6	8	9	4
PB3-6-4	1250	152	152	5.5	7	8	4
PB3-6-5	1525	152	152	5	6	7	4
PB3-6-6	2000	152	152	4.5	5.5	6	4
PB3-6-8	2500	152	152	4	5	5.5	4
PB3-6-10	3050	165	152	3.5	4.5	5	4
PB3-8-3	1000	203	203	12	16	18	5.5
PB3-8-4	1250	203	203	11	15	17	5.5
PB3-8-5	1525	203	203	10	14	16	5.5
PB3-8-6	2000	203	203	8	13	15	5.5
PB3-8-8	2500	203	203	7	11	13	5.5
PB3-8-10	3050	215	203	6	9	11	5.5
PB3-8-12	3650	215	203	5	7	9	5.5
PB3-10-4	1250	254	254	15	22	24	7.5
PB3-10-5	1525	254	254	14	20	22	7.5
PB3-10-6	2000	254	254	13	18	20	7.5
PB3-10-8	2500	254	254	11	16	18	7.5
PB3-10-10	3050	254	254	9	14	16	7.5
PB3-10-12	3650	270	254	8	12	14	7.5
PB3-12-5	1525	305	305	19	28	30	15
PB3-12-6	2000	305	305	17	24	26	15
PB3-12-8	2500	305	305	15	21	24	15
PB3-12-10	3050	305	305	13	19	22	15
PB3-12-12	3650	325	305	11	17	20	15
PB3-14-5	1525	356	356	29	37	40	22
PB3-14-6	2000	356	356	25	35	37	22
PB3-14-8	2500	356	356	22	32	35	22
PB3-14-10	3050	356	356	18	29	32	22
PB3-14-12	3650	370	356	15	27	30	22
PB3-16-5	1525	406	381	37	45	50	30
PB3-16-6	2000	406	381	33	40	45	30
PB3-16-8	2500	406	381	29	36	40	30
PB3-16-10	3050	406	381	25	32	35	30
PB3-16-12	3650	420	381	21	28	31	30
PB3-18-5	1525	457	432	44	55	60	45
PB3-18-6	2000	457	432	38	51	55	45
PB3-18-8	2500	457	432	35	45	48	45
PB3-18-10	3050	457	432	31	42	45	45
PB3-18-12	3650	480	432	28	38	40	45
PB3-20-5	1525	508	482	50	60	65	55
PB3-20-6	2000	508	482	45	55	60	55
PB3-20-8	2500	508	482	40	50	55	55
PB3-20-10	3050	508	482	35	45	50	55
PB3-20-12	3650	530	482	30	40	45	55
PB3-22-5	1525	559	510	56	82	87	70
PB3-22-6	2000	559	510	50	73	76	70
PB3-22-8	2500	559	510	45	65	68	70
PB3-22-10	3050	559	510	40	59	62	70
PB3-22-12	3650	590	510	37	55	58	70
PB3-24-5	1525	610	559	75	90	95	90
PB3-24-6	2000	610	559	65	80	85	90
PB3-24-8	2500	610	559	55	70	75	90
PB3-24-10	3050	610	559	50	65	70	90
PB3-24-12	3650	610	559	45	60	65	90

* TRD = Top Roll Diameter.

Prebending is a finished bending operation after only one pass.

Circular bending (Roll bending) is method of bending through several passes, hence the increased capacity.

CAPACITY TABLE PB4

Our machine sizes can handle plate thickness 1 - 250 mm (18 ga. – 10”).

We will guide you to the right machine to meet your specific requirements.

Don’t worry – we can bend almost everything!

		ROLL DIAMETERS			PREBENDING	CIRCULAR ROLLING		
MODEL	ROLL LENGTH	TOP	BOTTOM	SIDE	PB 3*TRD	RB 5*TRD	RB 8*TRD	MOTOR SIZE
PB4-4-3	mm	mm	mm	mm	mm	mm	mm	kW
	1000	105	102	102	3.5	4.5	5	2.2
	1250	105	102	102	3	4	4.5	2.2
	1525	105	102	102	2.5	3.5	4	2.2
PB4-4-6	2000	105	102	102	2	3	3.5	2.2
PB4-6-3	1000	152	152	140	6	8	9	4
PB4-6-4	1250	152	152	140	5.5	7	8	4
PB4-6-5	1525	152	152	140	5	6	7	4
PB4-6-6	2000	152	152	140	4.5	5.5	6	4
PB4-6-8	2500	152	152	140	4	5	5.5	4
PB4-6-10	3050	165	152	140	3.5	4.5	5	4
PB4-8-3	1000	203	203	160	12	16	18	7.5
PB4-8-4	1250	203	203	160	11	15	17	7.5
PB4-8-5	1525	203	203	160	10	14	16	7.5
PB4-8-6	2000	203	203	160	8	13	15	7.5
PB4-8-8	2500	203	203	160	7	11	13	7.5
PB4-8-10	3050	215	203	160	6	9	11	7.5
PB4-8-12	3650	215	203	160	5	7	9	7.5
PB4-10-4	1250	254	254	203	15	22	24	11
PB4-10-5	1525	254	254	203	14	20	22	11
PB4-10-6	2000	254	254	203	13	18	20	11
PB4-10-8	2500	254	254	203	11	16	18	11
PB4-10-10	3050	254	254	203	9	14	16	11
PB4-10-12	3650	270	254	203	8	12	14	11
PB4-12-5	1525	305	305	260	19	28	30	22
PB4-12-6	2000	305	305	260	17	24	26	22
PB4-12-8	2500	305	305	260	15	21	24	22
PB4-12-10	3050	305	305	260	13	19	22	22
PB4-12-12	3650	325	305	260	11	17	20	22
PB4-14-5	1525	356	356	315	29	37	40	30
PB4-14-6	2000	356	356	315	25	35	37	30
PB4-14-8	2500	356	356	315	22	32	35	30
PB4-14-10	3050	356	356	315	18	29	32	30
PB4-14-12	3650	370	356	315	15	27	30	30
PB4-16-5	1525	406	406	345	37	45	50	45
PB4-16-6	2000	406	406	345	33	40	45	45
PB4-16-8	2500	406	406	345	29	36	40	45
PB4-16-10	3050	406	406	345	25	32	35	45
PB4-16-12	3650	420	406	345	21	28	31	45
PB4-18-5	1525	457	457	390	44	55	60	67
PB4-18-6	2000	457	457	390	38	51	55	67
PB4-18-8	2500	457	457	390	35	45	48	67
PB4-18-10	3050	457	457	390	31	42	45	67
PB4-18-12	3650	480	457	390	28	38	40	67
PB4-20-5	1525	508	508	419	50	60	65	90
PB4-20-6	2000	508	508	419	45	55	60	90
PB4-20-8	2500	508	508	419	40	50	55	90
PB4-20-10	3050	508	508	419	35	45	50	90
PB4-20-12	3650	530	508	419	30	40	45	90
PB4-22-5	1525	559	559	457	56	82	87	110
PB4-22-6	2000	559	559	457	50	73	76	110
PB4-22-8	2500	559	559	457	45	65	68	110
PB4-22-10	3050	559	559	457	40	59	62	110
PB4-22-12	3650	590	559	457	37	55	58	110
PB4-24-5	1525	610	610	495	75	90	95	120
PB4-24-6	2000	610	610	495	65	80	85	120
PB4-24-8	2500	610	610	495	55	70	75	120
PB4-24-10	3050	610	610	495	50	65	70	120
PB4-24-12	3650	640	610	495	45	60	65	120
PB4-28-5	1525	711	711	571	90	115	125	165
PB4-28-6	2000	711	711	571	85	107	115	165
PB4-28-8	2500	711	711	571	80	99	106	165
PB4-28-10	3050	711	711	571	75	92	98	165
PB4-28-12	3650	740	711	571	70	85	90	165

* TRD = Top Roll Diameter.

Prebending is a finished bending operation after only one pass.

Circular bending (Roll bending) is method of bending through several passes, hence the increased capacity.

EXTENDED FEATURE

SEVEN – SWEBEND’S CNC CONTROL SYSTEM



THE POWER OF “SEVEN”

No two bending applications are the same. Many factors, including material size and thickness, mechanical properties, spring back, diameter, etc. can influence the bending requirements necessary to roll an acceptable part.

With the **SEVEN CNC** system, we can help take the guess work out of your rolling operation. The precision bending assistant IRMA, will easily accommodate for minor variations that are commonly found in all materials, which gives you the ultimate control over the entire rolling process.

Design any shape possible with **ADAM** – The Automated Design Assistant Manager and create precise production planning with the **SEVEN Simulator** which estimates the cycle time, runs the program in your preferred time-scale and calculates valuable data. Unsure of how much control you'll need? We'll optimize the number of CNC-controlled axes for your bending requirements.

- ✓ AVAILABLE IN MORE THAN 30 LANGUAGES!
- ✓ EASY, USER FRIENDLY GRAPHICAL INTERFACE
- ✓ TEMPLATES TO GET YOU UP AND RUNNING FAST



The SEVEN Control Panel




IRMA



ADAM



Easy, user friendly graphical interface.



Templates to get you up and running fast.



PERFECTLY MATCHED TO MEET YOUR REQUIREMENTS

The **SEVEN CNC** is available in several versions depending on your specific requirements. Choose from CPUs with differing processing speeds, touch screen monitors from 6.5” to 19”, enhanced software features and the number of CNC-controlled axes.

All **SEVEN CNC** systems feature components from Beckhoff of Germany, whose quality and worldwide presence ensures a stable hardware platform for many years to come. All systems come with online support via TeamViewer to assist you with programming questions and troubleshooting any issues with the machine.

In addition, the **SEVEN CNC** can be adapted to integrate your auxiliary equipment, such as robots, material handling equipment, etc.

FOR NEW & OLD MACHINES

We'll upgrade your old machine (with or without CNC) and train your operators in only three days!

BLUETOOTH CONTROL UNIT

Control your machine's functions from anywhere in the room. The Bluetooth protocol handles 24 digital signals (directional signals), 2 analog signals and 4 position signals (digital readouts). Thanks to the control unit's high adaptability it can control almost any type of bending machine in the industry.

Customized for you – you're the final voice,

SweBend will set up the control according to your wishes!

POWERFUL CONTROL

Equip your machine with our perfectly tuned and operator-friendly SEVEN CNC control system that will ensure market leading quality, greatly reduce previous production times and reduce learning time & skill training. Ask us about it!



UNMATCHED FREEDOM

As standard, your machine will be equipped with the SweBend Bluetooth Control unit, which is a hand-held wireless control unit that gives the operator full freedom to control all machine functions from anywhere in the room.



SERVICES

Owning a bending machine demands for a lot of attention to maintenance, training and living up to production requirements. For the experienced bender, this is second nature but can become too much when demand is high. We've developed and offer these services to face these problems and support bending machine owners (specialists) in their day-to-day business.



PERSONNEL TRAINING

Even the best machines require skilled operators, and therefore we offer training as well. This can be done in your workshop, using your specific equipment and products, in order to make it as efficient as possible. We offer general or customer-specific training programs for rolling, CNC controls (basic and advanced) and maintenance.



REFURBISHED MACHINES

Our large network of representatives and agents around the world are often able to supply new, used and refurbished bending machines for quick delivery. Turn to one of our resellers (page 13) for available machines.



SPARE PARTS

Even for the very best of machines, things can happen and you may need spare parts urgently. This could be an oil filter, a joystick, a push button, an encoder or a hydraulic valve, but regardless which part it is, do not hesitate to ask us for a quote. Be assured we will always do our utmost to get you the replacement part in the shortest possible time.



SERVICE & OVERHAULING

To get maximum performance from your machines, it is important to keep them in good shape. Let us perform your next service, and at the same time check the overall machine condition for you.

A smaller repair at an early stage is more economical than a unexpected breakdown later on (and those always come when things are really busy, don't they?). We also do full overhauling jobs, modifications and upgrades on old machines. This includes mechanical, hydraulic, electrical and CNC controls.

LONG TERM RESELLERS

SweBend continuously expand its network of resellers.

Ask us for a reseller close to You!



POWER MACHINERY
Australia
www.powermachinery.com.au
info@powermachinery.com.au



J VENEMA BV
Belgium, Holland, Luxembourg
www.venemabv.com
j.venema@venema-bv.com



TECTOOL
Brazil
www.tectool.com.br
tectool@tectool.com.br



W&D MACHINERY TRADING CO. LTD.
China
www.wd-beijing.com
weizhe@wd-beijing.com



PETRONIC S.R.O.
Czech Republic
www.petronic.cz
petronic@petronic.cz



I.P. MASKINER AS
Denmark
www.ip-maskiner.dk
info@ipmaskiner.dk



OY GRÖNBLOM AB
Finland
www.gronblom.fi
gronblom@gronblom.fi



MP PLUS
France
www.mpplus.fr
info@mpplus.fr



VENEMA BIEGETEC GMBH
Germany
www.venema-biegetec.com
info@venema-biegetec.com



SANMAC MACHINES
India
www.sanmacmachines.net
admin@sanmacmachines.com



PBS
Lithuania
www.pbs.lt
info@pbs.lt



TRILOGY MACHINERY, INC.
North America & Mexico
www.trilogymachinery.com
inquiry@trilogymachinery.com



MEIDELL
Norway
www.meidell.no
post@meidell.no



ERLANDSSON & HJORTH
Sweden
www.erlandsson-hjorth.se
info@erlandsson-hjorth.se



HILLI MASKIN
Sweden
www.hilli.se
mail@hilli.se



MASKINSERVICE
Sweden
www.maskinservice.nu
camilla@maskinservice.nu



METECH ENTERPRISE CO
Taiwan
www.metech-web.com.tw
info@metech-web.com.tw



TER THAI COMPANY LIMITED
Thailand
www.terthai.co.th
thisha_unn@yahoo.com



WJSUK LTD
United Kingdom
www.waterjetsweden.co.uk
info@wjsuk.com

POWERING THE WORLD'S LEADING BENDING COMPANIES

ABOUT SWEBEND

THE SWEBEND EXPERIENCE

At SweBend, we pride ourselves on creating a welcoming atmosphere where customers and agents feel valued and at home. This is achieved through our serious dedication to our work and respectful, honest interactions. We value long-term relationships and we stand by our promises, ensuring that our machines function exactly as we guarantee from the very first day.

“WE VALUE LONG-TERM RELATIONSHIPS AND WE STAND BY OUR PROMISES.”

In essence, the SweBend experience is about creating a home-like atmosphere, fostering long-term relationships, maintaining reliability, and providing exceptional customer care through honesty and deep knowledge. We are committed to upholding these values in every interaction and service we provide.

This is what we call
“the SweBend experience.”
/ Peter Nilsson, CEO & Sales



ABOUT SWEBEND

THE STORY OF SWEBEND



The story of SweBend originates with Roundo®, once considered the worlds best bending machine manufacturer, with clients such as Rolls-Royce, John Deere, Toyota, Volvo and over 16,000 machines delivered all over the world.

When the founder passed away, Peter Nilsson, whom he had mentored for almost 30 years, was appointed as his successor. Following a change of ownership at the company and the ensuing bankruptcy and closing of the Roundo factory in Sweden, Peter decided to work on a new venture, and joined by Roundo's best, brightest and most experienced team members, they combined their bending machine expertise – and SweBend was born.

Now, our sophisticated yet user-friendly machines supply the world's leading bending companies such as Barnshaws, Danvals, Den Oudsten, Kersten Europe, Sjölund, Van Rijsoort, etc. with perfect bending results which are produced effortlessly yet efficiently. Through innovation, profound quality thinking and unmatched engineering expertise, we take great pride in building machines that have the market's highest return on investment, a reason why so many loyal clients keep coming back to us to solve their toughest bending problems.

By breaking down our clients' bending challenges and then explaining to our customers the fundamental theory behind it, we produce modern, powerful and specifically purposed bending machines. The sophisticated functionality of our machines is easily

mastered by our clients as we assist them in becoming expert benders.

Located in Sweden, with renowned Swedish quality and a client-focused mindset, our passion for developing high-end bending machines has been recognized by clients all over the world. Through our vast knowledge of bending increasingly challenging materials, we continuously update our machines' technology with more sensors, better controls and improved software functionality. (Ask us about our renowned CNC system “SEVEN”; we can update old and even analog machines).

“WE PRODUCE MODERN, POWERFUL AND SPECIFICALLY PURPOSED BENDING MACHINES.”

Our clients value long term quality investments and choose the path of innovation, unmatched expertise and a powerful worldwide support network consisting of an increasing list of trusted resellers.

We look forward to working with you. Ask us about our section-, plate- and tube bending rolls, CNC systems, flighting, augers and spiraling machines, special rolls and tooling, and more!

The Roundo name is now a registered trademark of Faccin S.r.l.



PRECISION BENDING, SIMPLIFIED

THE WORLDS BEST BENDING MACHINES



MADE IN SWEDEN - BECAUSE QUALITY MATTERS

sales@swebend.com
+46 70 970 51 60

SweBend AB
Belevägen 6
281 43 Hässleholm
Sweden

www.swebend.com